


### **AGENDA**



- 1. Undercounter Reverse Osmosis Units
- 2. RO Booster pump & Filters
- 3. Standard Ecosoft undercounter unit
- 4. Horeca Reverse Osmosis Range
- 5. Replacement filters & housings
- 6. New Product Coming...
- 7. Ecosoft RSP list



## P'URE BALANCE



R 4525.00

### **Delicious water with Ca and Mg**

«AquaSpring» Technology
Refreshing water with balanced content of calcium and magnesium

«AquaGreen» Technology
Only 2 filter replacements per year
Saves up to 20 000 L of water per year

«Natural Flow» Technology Constant water quality

Safe water thanks to Dow membrane

12 L of pure water every hour

Easy installation, no need to mount on the wall



# Ecosoft Pressure Booster Pump for P'ure System



#### **Basic Information**

- This pump is used for the Ecosoft P'URE reverse osmosis filters.
- We recommend using this pump if the water pressure in your system is low (less than 3 bar) or unstable. This will ensure the filter works effectively and efficiently, and that water of the ideal quality will always be available on demand.
- This kit contains all the necessary components needed for connection.



## STANDARD RO FILTERS

#### **Standard 5-stage filter**

Safe water thanks to Ecosoft membrane



R 3499.00

#### Standard 6-stage filter

Small amount of minerals in purified water



#### Standard 5-stage filter with pump

For water supply systems with low pressure






## FILTER COMPONENTS





Feed valve

Drain saddle










Service wrenches











## REPLACEMENT FILTERS FOR RO

#### **Carbon post-filter**

Improves water taste



#### Mineralization filter

Enriches water with the essential minerals





## REPLACEMENT FILTER SET



R 220.00

**Set of RO replacement filters** 

For tap water

- 1. PP5
- 2. GAC
- 3. PP1



R 265.00

## Improved set of RO replacement filters

For tap water with high content of iron, chlorine and organic matter

- 1. PP5
- 2. GAC
- 3. CTO



## **ECOSOFT MEMBRANE**

- DOW Filmtec membrane sheet
- Stabilized salt rejection 97%
- 20% higher flow rate and
   20 minutes faster tank filling
- Resistant to fouling due to the higher spacer thickness
- Each membrane element is vacuum sealed.









## ECOSOFT STANDARD 3 STAGE FILTER



- 1. PP 5
- 2. ECOMIX D37
- 3. CTO

R 1699.00



# REPLACEMENT FILTER SET



Set of replacement filters For are with Hard Water 1 500 L

R 450.00







## ROBUST 1000 RO FILTER 60LT/H



R 9999.00



Ecosoft RObust reverse osmosis filters provide a sufficient amount of pure and safe water for HoReCa needs: for food and drink preparation, as well as delicious drinking water for guests and staff

- Pure water for hotels, restaurants and cafes
- Protection of appliances and equipment
- · Improved taste of drinks and dishes as well as clean, transparent ice
- Operates without pressure tank
- Compact and attractive design



## ROBUST PRO FILTER



R 14999.00

#### THE RIGHT WATER IN YOUR COFFEE HOUSE

- ✓ Approved by professional barista
- ✓ Suitable for dark and light roast coffee
- ✓ Water quality is in compliance with SCAA standards
- ✓ Saves water, 50 % recovery rate

Capacity	75 L/h
Water consumption	150 L/h
Membrane	1 x TW30-3012-500 GPD
Power consumption	0.08 kW



## ROBUST 3000 RO FILTER 145LT/H





R 31 999.00

#### Best suited for

Large restaurants, cafes and hotels that will make use of the combination of high performance and the compact filter size as it produces a large amount of high-quality water.

With this filter, you can get up to 3000 litres of purified water per day, which means there is enough water for everything, from a glass to cool, to larger amounts used for cooking in the kitchens

- Pure water for hotels, restaurants and cafes
- Protection of appliances and equipment
- Improved taste of drinks and dishes as well as clean, transparent ice
- Operates without pressure tank
- Compact and attractive design



## SEDIMENT FILTERS





Standard size	2.5" x 10"	
Connection size		3/4"
Flow capacity	10 L/min	
Operating pressure	3.5-4 bar	
Maximum pressure	6 bar	

### Filters for cold water

- Perfect for apartments with 1 bathroom
- > Transparent housing
- > Filter housing made of pure European first grade plastic
- Compact and easy to install

5-micron PP cartridge included



## SEDIMENT FILTERS





Standard size	2.5" x 10"
Connection size	1/2"
Flow capacity	10 L/min
Operating pressure	3.5-4 bar
Maximum pressure	8.6 bar
Water temperature	+3+80 °C

### Filter for hot water

- Perfect for apartments with 1 bathroom
- Ideal for hot water
- Filter housing made of pure European first grade plastic
- Compact and easy to install

5-micron PP cartridge included



# SEDIMENT REPLACEMENT FILTERS











## PP MELT BLOWN SEDIMENT FILTERS





Flow rate8 LPM30 LPMMaximum capacity10 000 L40 000 L6 months6 monthsFiltration rating5-micron5-micron

- ✓ High quality of purification
- ✓ Stable characteristics for retention of the particles
- ✓ European high melt flow PP
- ✓ Standard size



## PP STRING WOUND SEDIMENT FILTERS





Flow rate	8 LPM
Maximum capacity	10 000 L
	6 months
Filtration rating	5-micron

- ✓ High quality of purification
- ✓ Stable winding density characteristics
- ✓ Quality string from the Ukrainian manufacturer
- Protection of plumbing and fixtures
- √ Standard size




## DUAL GRADIENT PP SEDIMENT FILTERS





Flow rate	8 LPM	30 LPM
Maximum capacity	30 000 L	100 000 L
	6 months	6 months
Filtration rating	20 / 5 micron	20 / 5 micron


- √ 3 times higher rejection rates comparing to standard PP filters
- ✓ Low losses of pressures
- ✓ Stable operation even in case of water turbidity changes
- ✓ Superior quality, saving costs and space






## EFFICIENCY OF PARTICLES REMOVAL











## GAC REPLACEMENT FILTERS





Flow rate	1 LPM	5 LPM
Maximum capacity	10 000 L	60 000 L
	6 months	6 months
Water temperature	+343 °C	+343 °C

#### Granular activated carbon filters

- Reduction of chlorine and organic matter, improvement of taste, color and odor of water
- Made of 100% high-quality coconut shell carbon
- Filter housing made of pure European first grade plastic
- Contain a sediment post-filter to retain carbon particles
- Standard size



## CTO REPLACEMENT FILTERS





Flow rate	1 LPM	5 LPM
Maximum capacity	15 000 L	50 000 L
	6 months	6 months
Water temperature	+343 °C	+343 °C

### Granular activated carbon filters

- Reduction of chlorine, organic matter and sediments improvement of taste, color, and odor of water
- ➤ Made of 100% high-quality coconut shell carbon
- ➤ Filtration rating 10 micron
- > Uniformity of structure
- Standard size



Ecosoft replacement filter for iron reduction

#### **Key advantages**

- Reduction of iron up to 80%
- Full capacity up to 10 000 L
- · Stable operation and efficiency throughout the service life
- Filter housing made of pure European food grade plastic
- · Applicable for filters produced by other manufacturers

#### Benefits of using the filter

- · With timely replacement of the replacement filter, the filter will reduce the iron content in water.
- The water will become transparent, without an unpleasant red-brown color, the ferrous smell will disappear.
- Your home appliances that use water will last longer.

#### Maintenance

- · Before use, plunge a new replacement filter into cold water, and keep it submerged at least during 8 hours.
- The filter is recommended to be replaced every 3 months, regardless of the volume of consumed water.
- · After the filter replacement, discharge at least 10 liters of filtered water into the sewer.

#### **Specifications**

- · Recommended filtration flow rate 5.0 L/min
- · Service Life, not more than 6 months.
- 1mg/l Iron Limitation



R 749.00



## Ecosoft replacement filter with Ecomix® media

#### **Key advantages**

- · Transparent soft water without odor
- Full capacity up to 1 500 liters
- · Stable operation and efficiency throughout the service life
- Filter housing made of pure European food grade plastic
- · Suitable for filters produced by other manufacturers

#### Benefits of using the filter

- · Products will taste better
- Natural aroma and taste of tea and coffee
- Home appliances (kettle, iron, steam cooker etc.) will be protected from scale
- Purified water can be used to water flowers

#### Maintenance

- The replacement filter is intended for cold water only.
- Do not exceed the recommended filtration rate, this can lead to deterioration of water purification quality.
- After the filter replacement, discharge at least 10 liters of filtered water into the drain.
- The filter is recommended to be replaced every 3 months, regardless of the volume of consumed water.

#### **Specifications**

- · Recommended filtration flow rate 1.0 L/min
- · Service Life, not more than 6 months.



R 295.00



# Ecosoft replacement filter for hardness reduction

#### **Key advantages**

- · Hardness reduction
- · Affordable price for guaranteed quality
- Full capacity up to 500 L
- Filter housing made of pure European food grade plastic
- · Applicable for filters produced by other manufacturers

#### Benefits of using the filter

- · In case of timely replacement it prevents scaling while boiling water
- · Natural taste and aroma of tea and coffee
- · Home appliances (kettle, iron, steam cooker, air humidifier etc.) will stay protected from scale and malfunction related to scale

#### Maintenance

- The replacement filter is intended for cold tap water only.
- Do not exceed the recommended filtration rate, this can lead to deterioration of water purification quality.
- After the filter replacement, discharge at least 10 liters of filtered water into the drain.
- The filter is recommended to be replaced every 3 months, regardless of the volume of consumed water.

#### **Specifications**

- · Recommended filtration flow rate 1.0 L/min
- Service Life, not more than 6 months.



R 150.00

## New Product Coming...



## Thank you!



POWER
OF PURITY
ecosoft.com